



Declaration of Performance

According to the regulation (EU) No 305 of the European Parliaments and of the Council from 9th of March 2011

DoP Nr.: DoP004

Biofaser MBH

1. Type:	Medium boards MBH
2. Trade Name:	Biofaser Hardboard
3. Intended use:	Medium boards for non-load-bearing use in dry conditions
4. Manufacturer	FunderMax GmbH Klagenfurterstraße 87-89 A-9300 Sankt Veit an der Glan Austria
5. Construction product covered by:	EN 13986:2004+A1:2015
6. System of assessment and verification acc. to Annex V of the regulation (EU) No 305/2011:	System 4

FunderMax GmbH
Klagenfurter Straße 87-89
A-9300 St. Veit / Glan

Tel.: +43 (0)5 / 9494-0
Fax: +43 (0)5 / 9494-4200
office@fundermax.at
www.fundermax.at

DVR 0385344
Firmenbuchnummer: 90081y
UID-Nr.: ATU 26130102
Landesgericht Klagenfurt

RBI Raiffeisen Bank International AG
IBAN Nr. AT66 3100 0001 0033 2353
BIC: RZBAATWW

for
people
who
create

4

7. Declared Performance:

	Unit	Board thickness		
Mechanical properties	[mm]	≤ 10		
Internal Bound strength EN 13986	[N/mm ²]	0,10		
Bending strength EN 13986	[N/mm ²]	15		
Swelling in thickness, 24 h EN 13986	[%]	15		
Moisture content*1 EN 622	[%]	4 - 9		
Formaldehyde content EN ISO 12450-5	[mg/100g]	< 8		
Formaldehyde content DIN EN 16516	[ppm]	< 0,1		
Density	[kg/m ³]	< 900		
General tolerances				
Thickness tolerance EN 622	[mm]	± 0,3	± 0,5	± 0,7
Length and with tolerance EN 622	[mm]	± 5.0 / ± 3.0		
Squareness EN 622	[mm/m]	≤ 2.0		
Edge straightness tolerance EN 622	[mm/m]	≤ 1.5		
Tolerance on the mean density within a board EN 622	[%]	± 10		

FunderMax GmbH
Klagenfurter Straße 87-89
A-9300 St. Veit / Glan

Tel.: +43 (0)5/9494-0
Fax: +43 (0)5/9494-4200
office@fundermax.at
www.fundermax.at

DVR 0385344
Firmenbuchnummer: 90081y
UID-Nr.: ATU 26130102
Landesgericht Klagenfurt

RBI Raiffeisen Bank International AG
IBAN Nr: AT66 3100 0001 0033 2353
BIC: RZBAATWW

for
people
who
create


8

Building physical properties			
Fire behavior category according EN 13986 (> 5,0 mm; and < 900kg/m³)		D-s2, d0	
Water vapor diffusion resistance value EN 13986		μ moist	μ dry
Density < 900 kg/m³		20	30
Water vapor diffusion resistance value *3 EN ISO 12572		60	
Thermal conductivity EN 13986			
Density < 900 kg/m³		[W/(m*K)]	< 0.14
Sound absorption EN 13986			
Frequency range 250 Hz - 500 Hz		0.10	
Frequency range 1000 Hz - 2000 Hz		0.20	
Biological durability			
EN 335-3		Hazard category 1 (without earth contact; dry 20°C/65% RLF)	
Air sound insulation			
EN 13986		R = 13 x lg (mA) + 14 (mA = board density [kg/m²])	
PCP content EN 13986		[ppm]	< 5

*1 at delivery
*2 determined by testing

Note:
This document has been drawn up to the best of our knowledge and with special diligence. We accept no liability for any mistakes, errors in standards or printing errors. In addition, technical modifications can result from the continuous further development, as well as from changes in standards and documents originating from statutory bodies. The contents of this technical leaflet should therefore not be considered as instructions for use or as legally binding.

St. Veit / Glan 07.04.2020
(Place and Date)


.....
ppa. Gerhard Jannach
Vice President, Innovation- and Technology Management


.....
Marlen Streicher
Head of, Quality Management St. Veit/Glan

FunderMax GmbH
Klagenfurter Straße 87-89
A-9300 St. Veit / Glan
Tel.: +43 (0)5/9494-0
Fax: +43 (0)5/9494-4200
office@fundermax.at
www.fundermax.at

DVR 0385344
Firmenbuchnummer: 90081y
UID-Nr.: ATU 26130102
Landesgericht Klagenfurt
RBI Raiffeisen Bank International AG
IBAN Nr. AT66 3100 0001 0033 2353
BIC: RZBAATWW

for
people
who
create

