

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

Particleboard of the technical classes P4, P5, P6 and P7

according to the product specification listed in the current addendum to this certificate produced by

Company
FUNDERMAX GMBH
Bickfordstraße 6
AT-7201 Neudörfl

and produced in the manufacturing plant

AT-7201 Neudörfl, Bickfordstraße 6

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 13986:2004+A1:2015

under system 2+ being certified for the performances set out in this certificate are applied and that the factory production control fulfils all the prescribed requirements for these performances.

Certificate number: 1359-CPR-0682 Date of first issue: 12.05.2016 Date of issuance: 12.05.2016

This certificate will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard used to assess the performances of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the certification body for the factory production control.

For the validity of this certificate see www.holzforschung.at.

Dr. Andreas Neumüller

Authorised signatory

Dr. Manfred Brandstätter Head of the Certification Body

Annex to Certificate 1359-CPR-0682

Date of issue: 12.05.2016



Scope of certification for the following products:

Product: Particleboards for load bearing purposes

for use under dry conditions

Technical class: P4 according to EN 312

Thickness range: 6 - 40 mmFire performance: D-s2, d0

Formaldehyde emission class: E1

Product: Particleboards for load bearing purposes

for use under humid conditions and for use as

structural floor decking on joists

Technical class: P5 according to EN 312

Thickness range: 6 - 40 mmFire performance: D-s2, d0

Formaldehyde emission class: E1

Product: Particleboards for heavy load bearing purposes

for use under dry conditions

Technical class: P6 according to EN 312

Thickness range: 6 - 40 mmFire performance: D-s2, d0

Formaldehyde emission class: E1

Product: Particleboards for heavy load bearing purposes

for use under humid conditions

Technical class: P7 according to EN 312

Thickness range: 6 - 40 mmFire performance: D-s2, d0

Formaldehyde emission class: E1